EMERGENCY SHOWER & EYEWASH STATION

A combined, floor-mounted station for emergency body showering and eye flushing.





TWO FUNCTIONS

Body shower

Overhead shower with stainless steel pull rod.

Dual eyewash

Twin outlets with protective yellow caps.

Push control

Clearly marked hand-operated eyewash valve.

Stainless steel basin

Collects eyewash water and directs it towards the drain.

250 mm shower head

Corrosion-resistant ABS head with a high-visibility yellow finish.

Floor-mounted design

Upright station with a base flange and plumbed water connections.

Request price & availability

info.brandexper@gmail.com
Bombo Road, Nalubega Complex, Kampala

PRODUCT SPECIFICATIONS

Technical details supplied in the product images.

Water pressure	0.2-0.4 MPa (2-4 bar)
Eyewash flow rate	>12 L/min
Shower flow rate	>75.7 L/min
Water inlet	1-1/4 inch female NPT thread
Water outlet	1-1/4 inch female NPT thread
Overall height	2,300 mm
Shower head height*	2,100 mm
Eyewash basin height*	1,040 mm
Shower arm dimension*	610 mm
Shower head diameter	250 mm
Eyewash basin width*	260 mm

*Dimensions as illustrated in the supplied product diagram.



SUPPLIED UNASSEMBLED

Packed as separate components for shipment and assembly.

Components pictured
Shower head, pipe sections, base flange, eyewash basin, twin-nozzle assembly, push valve, pull rod, fittings, fasteners, seal and safety sign.

Assembly and connection to a suitable water supply and drainage system are required before use.

Product information is based on the supplied images. Confirm the exact model, final configuration and installation requirements when ordering.